

THERMO-ELECTRIC COOLERS

Classic Model M425

Perma Pure's Baldwin™ Classic Series Model M425 features a unique slim design leaving additional space to install or access other sample conditioning system components. The M425 is a great choice for moderate flow rate single stream or dual stream applications.

Physical Description

Single (Series) / Dual (Parallel) Channel System
 2 x 5" Heat Exchangers connected in series or parallel
 2 Active (cooled to 4°C) Heat Exchangers
 LCD temperature display



Operating Specifications

Sample Gas Flow Range	3-5 LPM 6.5-10.8 SCFH
Inlet Dew Point at Rated Flow	140°F @ 20% H ₂ O, 5 LPM 60°C
Dimensions	11.20 x 7.25 x 11.20 in. HWD 28.5 x 18.4 x 28.5 cm
Weight	17 lbs 7.7 kg
Maximum Inlet Sample Temperature	392°F (200°C) SS, Glass Impingers 280°F (138°C) Kynar® Impinger
Maximum Inlet Pressure	45 psig 3 bar / 2250 mmHg
Maximum Heat Exchanger Pressure Drop	<+1 in. H ₂ O
Ambient Temperature Range	33-104°F 0.56-40°C
Outlet Sample Gas Dew Point	41°F 5°C
Inlet Tubing Connection	3/8 in. FNPT
Outlet Tubing Connection	1/4 in. FNPT
Drain Tubing Connection	3/8 in. FNPT
Voltage	110 (220 optional) VAC 50/60 Hz
Thermoelectric Elements	40 mm
Power Supply	250W
Cooling Down Time	Less than 3 minutes

Baldwin™ is a Trademark of Perma Pure LLC
 Kynar® is a Registered Trademark of Alf Autochem of North America



ETA Associates

119 Foster Street, Bldg #6 • Peabody, MA 01960

Tel: (978) 532-1330 • Fax: (978) 532 7325 • www.ETAassociates.com • eta@ETAassociates.com

